



Series 6 - MOCSY7 75 Ohm Broadband Coaxial Cable

Drop Cable

Series 6 standard shield 60 % braid 75 ohm

RoHS 2002/95/EC compliant - all constructions

Part Number	Description	Regulatory Compliance		
		Agency	NEC 820	NEC 830
A660-BVV	black PVC jacket	UL/ETL Certification	CATV, CM	BM
AZ660-BVV	Z-Wire®	UL/ETL Certification	CATV, CM	BM
HZ660-BVV	TRITON™, Z-Wire®	UL/ETL Certification	CATV, CM	BM
A660DL-BVV	dual	UL/ETL Certification	CATV, CM	BM
A660-BF	flooded	UL/ETL Certification		BMU
H660-BF	flooded, TRITON™	UL/ETL Certification		BMU
A660-BVM	messenger			
AZ660-BVM	messenger, Z-Wire®			
HZ660-BVM	messenger, TRITON™, Z-Wire®			
A660-BVR	riser rated	UL/ETL Certification	CATVR, CMR	BMR

Construction Materials

Dielectric	Foam PE
Inner Conductor	Copper-clad steel wire
Outer Conductor	Bonded foil + 60 % aluminum braid
Messenger (if applicable)	0.051 in galvanized steel

Dimensions

Diameter Over Dielectric	4.490 mm (0.177 in)
Diameter Over Jacket	6.860 mm (0.270 in)
Diameter Over Tape	4.700 mm (0.185 in)
Inner Conductor OD	1.024 mm (0.0403 in)
Jacket Wall Thickness	0.760 mm (0.030 in)

Electrical Specifications

Operating Frequency Band	5 to 1525 MHz
Cable Impedance	75 ohm
dc Loop Resistance	135.0 ohms/km (41.1 ohms/kft)
dc Test Voltage	1500 volts
Jacket Spark Test Voltage (rms)	2500 volts
Velocity	85 %
Attenuation	See page 22

Mechanical Specifications (if applicable)

Messenger Breaking Strength	77.1 kgf (170.0 lbf)
-----------------------------	----------------------

Ordering Information (choose one from each column)

							Description
A							MOCSY®7 subscriber access cable
AZ							MOCSY®7 subscriber access cable Z-Wire® anti-corrosion protection
H							MOCSY®7 TRITON™ enhanced base shield tape
HZ							MOCSY®7 TRITON™ enhanced base shield tape with Z-Wire® anti-corrosion protection
	6						Series 6 braided cable
		60					60 % braid coverage
			DL				Dual
				-BF			Bonded foil, PE jacket, flooding compound
				-BVM			Bonded foil, PVC jacket, messenger wire
				-BVR			Bonded foil, PVC jacket, riser rated
				-BVV			Bonded foil, PVC jacket, UL CATV rated
					-X		Jacketing - black (leave blank), neutral (N), orange (O), white (W)
							Packaging - reel (leave blank)
					-BOX		Packaging - box
					-CAD		Packaging - coil, for reusable caddy
					-RBX5		Packaging - reel-in box, 500 ft

